

# DP8340 Series

## Versatile Compact Receipt / Record Printers



- ✦ Reliable budget entry level printer
- ✦ Black and red printing
- ✦ Separate 230v AC power supply with 12v DC output
- ✦ 4.5" / 115 mm paper width

**DP8340FD – Serial Friction Black/Red Printer**  
**DP8340FC – Parallel Friction Black/Red Printer**  
**DP8340SD – Serial Sprocket Black/Red Printer**  
**DP8340SC – Parallel Sprocket Black/Red Printer**

### Typical Applications

#### Receipt Printer

POS systems  
 Credit card authorisation  
 Kitchen/remote printer

#### Mobile Printing

12 volt applications

#### Label Printing

Sprocket version


#### Record Printer

Data logging  
 Measuring equipment

#### Graphics Version

Details upon request

### Dimensions



### DP8340 Printer Specifications

<b>Printer Method</b>	9-pin serial impact dot matrix	<b>Paper Feed Speed</b>	12 Lines per second
<b>Print Speed</b>	Up to 2 lines per second (bi-directional)	<b>Paper</b>	
<b>Number of Columns</b>	40 (12 CPI) 48 or 60 column option	<b>DP8340</b>	Roll Paper (Width 4.5" / 115 mm)
<b>Print Area</b>	84.3 mm	<b>DP8340S</b>	Sprocket fanfold (Width 4.5" / 115 mm)
<b>Line Spacing</b>	1/6"	<b>Roll Diameter</b>	Max. 3.15" (80 mm)
<b>Character Size</b>	12 CPI	<b>Thickness</b>	Max. 64gsm
<b>Character Set</b>	ASCII 96, International and Symbol 64, Block graphics 64, IBM Special 83 & Block graphics 50 (available only on parallel interface), Download 10 (available only on parallel interface)	<b>No. of Copies</b>	One original + 1 copy
<b>Character Matrix</b>		<b>Operating Conditions</b>	5°C to 40°C, 10% to 80% RH (w/o condensation)
<b>Ordinary Characters</b>	5 x 9 dots	<b>Storage Conditions</b>	-20°C to 70°C, 5% to 95% RH (w/o condensation)
<b>Block Graphics</b>	6 x 6 dots	<b>Data Buffer</b>	Approx. 1.5Kb
<b>IBM Block Graphic</b>	6 x 8 dots (available only on parallel interface) Graphic Mode	<b>Interface</b>	Serial (RS232C) or Parallel
<b>Ink Ribbon</b>	Black/Red (SF-03BR), Life 800,000 / 400,000 characters	<b>Dimensions</b>	202 (W) x 200 (D) x 98 (H) mm (w/o paper holder)
<b>Option</b>	Black (SF-03B), Life 800,000 characters	<b>Weight</b>	Approx. 1.9Kg
<b>Reliability</b>	10 million lines Calculated Real Time MCBF 5 million lines MCBF Traditional	<b>Windows Driver</b>	Available
<b>Print Head</b>	70 million characters	<b>Peripheral Drive</b>	RS232C - 1 output / Parallel 2 outputs 12V / 1A max.
		<b>PS8340 Power Supply Unit</b>	
		<b>Output</b>	DC 12V ± 10% (max. 2A)
		<b>Dimensions</b>	59 (W) x 117 (D) x 36 (H) mm
		<b>Weight</b>	0.2Kg

